



High Efficient Rectifier



Features

- High efficiency
- High current capability
- High Reliability
- High surge current capability
- Glass passivated chip junction
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Mechanical Data

- **Package:** R-6
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Color band denotes cathode end

■Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	HER601 G	HER602 G	HER603 G	HER604 G	HER605 G	HER606 G	HER607 G	HER608 G
Device marking code			HER601 G	HER602 G	HER603 G	HER604 G	HER605 G	HER606 G	HER607 G	HER608 G
Maximum Repetitive Peak Reverse Voltage	VRRM	V	50	100	200	300	400	600	800	1000
Maximum RMS Voltage	VRMS	V	35	70	140	210	280	420	560	700
Maximum DC blocking Voltage	VDC	V	50	100	200	300	400	600	800	1000
Average Forward Current @60Hz sine wave, Resistance load, Ta=65°C	IF(AV)	A	6.0							
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, Tj=25°C	IFSM	A	200							
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25°C			400							
Current squared time @1ms≤t≤8.3ms Tj=25°C, Rating of per diode	I²t	A²s	166							
Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	Cj	pF	150			83		81		
Storage Temperature	Tstg	°C	-55 ~ +150							
Junction Temperature	Tj	°C	-55 ~ +150							

■Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	HER601 G	HER602 G	HER603 G	HER604 G	HER605 G	HER606 G	HER607 G	HER608 G
Maximum instantaneous forward voltage drop per diode	VF	V	IFM=6.0A	1.0			1.3		1.7		
Maximum DC reverse current at rated DC blocking voltage per diode	IR	µA	Tj=25°C	2.5							
			Tj=125°C	150							
Maximum reverse recovery time	tr	ns	IF=0.5A, IR=1.0A, IIR=0.25A	50					75		



HER601G THRU HER608G

■ Thermal Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	HER601G	HER602G	HER603G	HER604G	HER605G	HER606G	HER607G	HER608G
Typical Thermal Resistance	R _{θJA}	°C/W	15							

■ Ordering Information (Example)

PREFERRED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
HER601G~HER608G	D1	Approximate 1.95	500	500	5000	Tape
HER601G~HER608G	C1	Approximate 1.95	100	100	5000	Bulk

■ Characteristics (Typical)

FIG.1: I_o-T_a Curve




FIG.2: Forward Surge Current Capability




FIG.3: Forward Voltage






FIG.4: Typical Reverse Characteristics






HER601G THRU HER608G

FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■ Outline Dimensions



R-6		
Dim	Min	Max
A	8.60	9.10
B	8.60	9.10
C	25.4	/
D	1.20	1.32



HER601G THRU HER608G

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.